

*i*SEP™ 500

Fresh water scarcity is one of today's most pressing issues, forcing both industry and municipalities to look at water in a new light. iSepTM ultrafiltration (UF) membrane modules are helping solve today's water problems by working on some of the most difficult water reuse and wastewater treatment applications at a lower cost.


When it comes to UF membrane performance, not all designs are created to handle extreme feed water parameters. Many UF products are simply unable to withstand the rigors of wastewater treatment or peak solids in water treatment. *i*Sep modules are built to handle the toughest waste streams, ensuring system owners see the same consistent and reliable performance time and time again.

BETTER PERFORMANCE AT A LOWER COST

 $\it i$ Sep modules were specifically designed to lower UF treatment costs on challenging water and wastewater applications.

- Toughest flat-sheet UF membrane
- Unique module design
- Lowest operating cost
- Superior filtrate quality

Elimination of extensive UF pre-treatment, especially for wastewater treatment and high-solids water treatment applications, coupled with ultra-low energy and chemical consumption provides an extremely low total cost of ownership.





Produced water feed turned into iSep filtrate

FEATURES AND BENEFITS

- Vacuum-driven operation > Ultra-low energy
- Spiral-wound flat-sheet UF membrane > No fiber breakages
- Proprietary backwashable membrane with air scouring capability > Increased cleanability
- Low fouling feed channel design > Ultra-low chemical consumption
- Skid mounted integrated tank design > **Simple operation**

TOUGH MEMBRANE MODULE

Wastewater applications can be both aggressive and unrelenting, often pushing membrane operation beyond their limits. The patented iSep membrane design is easily cleaned, even after major process upsets and solids spikes, thus eliminating irreversible fouling. The tough and forgiving membrane ensures unsurpassed effluent quality over the entire life of the element.

HIGHEST EFFLUENT QUALITY

With a robust membrane and innovative module design, iSep eliminates fiber breakage and membrane plugging issues commonly associated with conventional hollow-fiber UF membrane. iSep provides reliable and consistent performance needed for today's demanding wastewater and difficult-to-treat water applications.

MAXIMUM FEED LIMITS*

TSS	1000 mg/l
BOD	150 mg/l
OIL & GREASE	100 mg/l

^{*}Higher values can be treated

TYPICAL iSEP FILTRATE QUALITY

TSS	< 1.0 mg/l
Turbidity	≤ 0.1 NTU
SDI	≤ 3



*i*SEP™ 500 Application Experience

















The low fouling design of *i*Sep membranes enable it to operate on some of the most challenging water and wastewater streams:

- Produced Water
- River Water
- Power Plant Wastewater
- Secondary & Tertiary Wastewater
- Food & Dairy Wastewater
- Industrial Wastewater

MICRODYN-NADIR has found success installing iSep for some of the toughest applications:

- Peak Flow Management
- Leachate Treatment
- RO Pretreatment

EUROPE

Germany: +49 611 962 6001 Italy: +39 0721 1796201 info@microdyn-nadir.com

AMERICAS

USA: +1805 964 8003 sales.mnus@microdyn-nadir.com

ASIA

APAC: +65 6457 7533 China: +86 10 8413 9860 waterchina@mann-hummel.com



